

BF



BF 3000

MAXIMAL 120++ AMPERE SPITZENSTROM FÜR 10 SEKUNDEN
MAXIMAL 70++ AMPERE DAUERSTROM

DATEN

Nominal capacity and voltage	2300 mA/13,2V
Recommended standard charge method	3A to 14,4CCCV/45 Min.
Recommended fast charge current	10A to 14,4CCCV/15 Min.
Maximum continuous discharge	70A
Pulse discharge at 10 sec	120A
Cycle life at 10C discharge, 100% DOD	über 1100 Zyklen
Recommended charge and cut-off V at 25°C	14,4V to 8V
Recommended charge and cut-off V below 0°C	16V to 2V
Operating temperature range	-30°C to +60°C
Storage temperature range	-50°C to +60°C
Battery weight	<475 g

BF 5000

MAXIMAL 240++ AMPERE SPITZENSTROM FÜR 10 SEKUNDEN
MAXIMAL 140++ AMPERE DAUERSTROM

DATEN

Nominal capacity and voltage	4600 mA/13,2V
Recommended standard charge method	6A to 14,4CCCV/45 Min.
Recommended fast charge current	20A to 14,4CCCV/15 Min.
Maximum continuous discharge	140A
Pulse discharge at 10 sec	240A
Cycle life at 10C discharge, 100% DOD	über 1100 Zyklen
Recommended charge and cut-off V at 25°C	14,4V to 8V
Recommended charge and cut-off V below 0°C	16V to 2V
Operating temperature range	-30°C to +60°C
Storage temperature range	-50°C to +60°C
Battery weight	<850 g

BF 7000

MAXIMAL 360++ AMPERE SPITZENSTROM FÜR 10 SEKUNDEN
MAXIMAL 210++ AMPERE DAUERSTROM

DATEN

Nominal capacity and voltage	6900 mA/13,2V
Recommended standard charge method	9A to 14,4CCCV/45 Min.
Recommended fast charge current	30A to 14,4CCCV/15 Min.
Maximum continuous discharge	210A
Pulse discharge at 10 sec	360A
Cycle life at 10C discharge, 100% DOD	über 1100 Zyklen
Recommended charge and cut-off V at 25°C	14,4V to 8V
Recommended charge and cut-off V below 0°C	16V to 2V
Operating temperature range	-30°C to +60°C
Storage temperature range	-50°C to +60°C
Battery weight	<1300 g

Durch mitgelieferte Steckverbindungen ist die BF-Batterie-Serie für jeglichen Einsatz passend vorbereitet.



BF AKKU . DE

info@bfakku.de · Hotline +49 (0) 59 21-1 79 21 92 · Fax +49 (0) 59 21- 1 79 21 93